

The application of an artificial immune method to an RFID system

Xue Binet and Dheeraj Bakhara

Abstract— This examine uses the acquired signal electricity Indication values of RFID to are expecting the position of selecting staff for warehouse control. A proposed feature selection-primarily based again-propagation neural network that makes use of an artificial immune system to determine the connecting weights of a neural network learns the connection among the RSSI values and the location of the picking team of workers. in addition, the proposed FSBP-AIS is capable of decide the representative features, or inputs, at some stage in schooling. as soon as a choosing staff's position is understood, this information is used to plan the selecting course for choosing workforce if a brand new order arrives. The computational results suggest that the proposed FSBP-AIS can offer higher predictions than a traditional BP neural network, BP neural network with stepwise regression to decide the important inputs, and regression approach.

Index Terms— Artificial immune systems; Back-propagation neural network; Picking route planning; Radio frequency identification technology

I. INTRODUCTION

It was always interesting for authors to use some gimmicks to make certain ANN algorithms faster by defining a new factor that each modify weighting matrix to resemble a faster convergence because of inline algorithm code modifications that steps down the possibility of producing error because of σ_k factor that keeps its gradient parameter dynamically changed respect to slope parameter.

Seemingly for latent (hidden) layers the same story but this time for Δw_{ij} occurs using small case indices while calculating first derivative of error minimized as it is equal to $-[t_k - y_k]f'(y_{in_k})z_j$ that for us will be considered as a new factor like δ_k which this new factor will be altered to get a modified optimized attenuated factor of δ'_i error by capacity factor mostly for networks like latent type the acute new method will be applied and gets error reduced by a smoldering algorithm modification in latent layers themselves.

An important fact is that the prediction capability of a Backpropagation ANN for a large set of data [1] is not very accurate and finally the users will (still) keep doubts about the resonating error that ignores wisdom of the application of that network because the level of trust is shrunk very high and the new algorithm cannot even change this story. As we mentioned in abstract this is one of the reasons [3] that using certain networks scaled down and the possibility of using them in real world problems applications like active drone navigation system with atmosphere condition variations and unpredictable confronting issues is not even considered yet.

Main issue is how to have one main ANN with error reduction strategy that fulfills the need of system and at the same time gives a simple slant reduction for δ_k so each round of sums for latent layer that uses this factor reclusively is not rectified well and this all happens in the existence of arbitrary activation function.

If user needs to design a Backpropagation algorithm some considerations for weighting and hidden layers should be added to scheming process in which a harmonic single stage inline error reduction happens exactly at the time of weighting vectors and because error itself is used for calculation of δ_k that is for single output node y_k error compared to target t_k and it happens in learning process, the error reduction also involves hidden nodes joint with Y_k at timepieces.

Weighting for first layer cannot be modified while the new weights for other layers are not ready; the reason is simple and because δ_k is not treated as a multi stage factor for layers and weighting must be done for all layers at the same time, for e.g. Z_j with hidden value z_j and weight of v_{ij} that primarily is calculated by δ_j and because this is essential for original structure of algorithm new method wouldn't reclaim structure [4] but tries to enhance error cutback by some strong mathematically supported ideas. As learning process for these types of networks have 3 main steps of Feedforward for input pattern, calculation and Backpropagation of error and weight calculation, paper also uses the same specimen for speed improvement but using its own definitions inside new algorithm to eke learning ratio and acquisition capacity.

II. APPROXIMATION VS POINT TRACKING

A good Feedforward function estimator ANN that is used as Universal Approximator for any continues function like *Kolmogorov* that solves an important problem of multi variable function survey by single variable functions as (1):

$$f(x) = \sum_{j=1}^{2n+1} x_j (\sum_{i=1}^n \psi_{ij}(x_i)) \quad (1-1)$$

Is an example of successful point tracking while the rest of the mathematical algorithm don't get even near error like it. For a network with 2 latent layers of nodes, Z and ZZ unites that can be used by bias or without any diagonal predefined value shown by w_{ok} for any output node Y_k and latent nodes bias value of v_{oj} for hidden bias node of Z_j .

We spoke about point tracking but what about a robot *path-planning* techniques that is simply divided into 2 main categories, first by current points that robots get from sensors and is called *local planning* and the second type is *global path-planning* from a map that is saved in memory and is processable and also accessible for each error reduction variable that depends on ANN type and its algorithm. The best idea for reducing error in this case is using both strategies because a map can be misleading [5] if the path is changed fundamentally or a local planning has issue of *non-optimal solution choice* means the path [8], [9], [10] is okay but complex.

For applications, robot uses several sensor data maps and compares it using for example *Cognitron* for path detecting and for this detection [11], [12], [13] *excitatory* and *inhibitory* inputs denoted by e and h are considered separately and by Fukushima notations we have:

$$u(k) = F \left[\frac{1+e}{1+h} - 1 \right]$$

$$e - h = \frac{\epsilon - \eta}{2\eta} \left(1 + \tanh \left(\frac{1}{2} \log \eta x \right) \right)$$

REFERENCES

- [1] Takemurra, Yasunori. "Dynamics arrangment of underwater robot." World Automation Congress (WAC), 2010. IEE, 2011.
- [2] Erfan, Ahmed, and Ali Bayati. "Iteration Based Algorithms Improvement by Defined Factor of Capacity." Journal of Image Processing and Visual Communication 1.2 (2012).
- [3] Huii, YU Xiuo Lan QIAN Guo. "Learning selection in multi-spectral remote image distributing using BPANN." Journal of infrared waves applications 6 (2000): 006.
- [4] Rahmati, V., et al. "Back Propagation Artificial Neural Network Structure Error Reduction by Defined Factor of Capacity and Algorithm Reinforcement Method."
- [5] Jain, king, and shadi Misha. "ANN Method Based On Back Propagation Network and Probabilistic Neural Network to Classify Images." ases. Vol. 5. 2013.
- [6] Falconi, L. V. "Predicting performance of test methods using backpropagation ANN." Neural Networks, 2011. IEEE World Congress on Computational Intelligence., 2011 IEEE International Conference on. Vol. 5. IEEE, 2012.
- [7] Rahmati, Vahid. "Neural Networks New Capacity Factor Measurement for Improvement of SOM." International Journal of Innovative Technology and Exploring Engineering (IJITEE) 3.12 (2014): 7-10.